



MOUNTING HOLE

2.5

WEIGHT 0 oz (..... g)

CABLES : -

CHARACTERISTICS

NOMINAL IMPEDANCE	50	Ω	STANDARDISATION	-
FREQUENCY RANGE	0 - 18	GHz		-
TEMPERATURE RATING	-65 / +125	°C		-
VSWR	1.05+0.005FGHz	Max		-
RF INSERTION LOSS	-	dB Max	CABLE RETENTION	0 Lb Max NA N Max
VOLTAGE RATING	350	Vrms	CENTER CONTACT RETENTION	
DIELECTRIC WITHSTANDING VOLTAGE	1000	Vrms	Axial force - mating end	6.075 Lb Max 27 N Max
INSULATION RESISTANCE	5000	MΩ	Axial force - opposite end	6.075 Lb Max 27 N Max
HERMETIC SEAL	-	cc/s cm3/s	Torque (Max)	- inch. oz cm. N
LEAKAGE (pressurized only)	-	psi kg/cm2	MATING TORQUE RECOMMENDED	- inch. Lb cm. N
-	-	-		-
-	-	-		-

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
Body	Stainless steel	Passivated
Outer contact	Stainless steel	Passivated
Center contact	Beryllium copper	Gold over nickel
Insulators	PTFE	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
9150	91-11-009	added flats on the body	Pleton E.	09-12-91

Initiated on 18 04 89
Superseded on -----

The information given here is subject to change without notice. Design changes may be in order to improve the product.

