



MOUNTING HOLE

4  
WEIGHT oz ( g) cables:

CHARACTERISTICS

NOMINAL IMPEDANCE	50	Ω
FREQUENCY RANGE	0 - 24	GHz
TEMPERATURE RATING	-65/+105	°C
VSWR	-	Max
RF INSERTION LOSS	-	dB Max
VOLTAGE RATING	250	Vrms
DIELECTRIC WITHSTANDING VOLTAGE	675	Vrms
INSULATION RESISTANCE	5000	MΩ
HERMETIC SEAL	NA	cc/s cm <sup>3</sup> /s
LEAKAGE (pressurized only)	-	psi kg/cm <sup>2</sup>

STANDARDISATION

CABLE RETENTION

CENTER CONTACT RETENTION

Axial force - mating end	8.00
Axial force - opposite end	8.00
Torque (Min)	NA

RECOMMENDED TORQUES

Mating	NA
Panel nut	NA
Clamp nut	NA

CONSTRUCTION

CONNECTOR PARTS	MATERIALS	FINISH
BODY	Stainless steel	Passivated
OUTER CONTACT	-	-
CENTER CONTACT	Beryllium copper	Gold over nickel
INSULATORS	PTFE	-
-	-	-
-	-	-
-	-	-
-	-	-

ISSUE	REVISION No	DESCRIPTION	BY	DATE
.	.	.	.	.
.	.	.	.	.
.	.	.	.	.

Initiated on 29-JAN-90

The information given here is subject to change without notice. Design changes may be made in order to improve the product.



Superseded on