



**MATERIAL:**  
CONTACT BODY : BERYLLIUM COPPER PER ASTM B 196  
PROTECTION SLEEVE : STAINLESS STEEL PER SAE AMS-5514

**FINISH:**  
CONTACT BODY : PLATING .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER SAE AMS-2403

**WIRING INSTRUCTIONS:**  
WIRE ACCOMMODATED : AWG 14  
INSULATION DIAMETER : 3,40 max (.134)  
STRIP LENGTH : 6 (.354)

**TOOLING : (ORDERED SEPARATLY)**  
CRIMPING TOOL : M22520/1-01 (RADIALL P/N : 282291)

POSITIONER : M22520/1-02 (RADIALL P/N : 282972)  
SELECTOR POSITION : 6 FOR AWG 14

INS/EXT TOOL : M81969/1-03 (RADIALL P/N : 282546)

DIMENSIONS : mm (inch are given for information only)

CREATION					
PEN:					
NOM:	MONDOT JC.				
DATE:	JULY 08, 2009				
APPR.:	MAGARI JP.	/	/	/	/
	Issue	Revisions	Name	Approved	

616339EN

RADIALL PROPRIETARY INFORMATION