

WIRES ACCOMMODATED : AWG 12 AND 14  
INSULATOR DIAMETER : .135 MAX (3.43)  
STRIP LENGTH : .236 (6,00)


TOOLING  
CRIMPING TOOL : M22520/1-01 (RADIALL 282 291)  
SELECTOR POSITION : 8 FOR AWG 12  
7 FOR AWG 14

POSITIONER : M22520/1-11 (RADIALL 282 579)

MATERIAL AND FINISHES :  
BODY CONTACT : COPPER ALLOY (C97) HEAT TREATED HARDNESS 200 HV  
BARREL ANNEALED HARDNESS 60-80 HV

PLATING : .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER SAE AMS-QQ-N-290

INSERTION/EXTRACTION TOOL : M81969/28-02 (RADIALL 282 547)  
SPL RADIALL EXT. 282 945



DIMENSIONS : mm (inch are given for information only)

**CREATION**

PEN:

NOM: VALGRESY

DATE: AUG 20 2008

APPR.: BROCHET

Issue	Revisions	Name	Approved
/	/	/	/
/	/	/	/
/	/	/	/
/	/	/	/
/	/	/	/

618240EN

RADIALL PROPRIETARY INFORMATION