



WIRES ACCOMMODATED : AWG 12 AND 14  
INSULATOR DIAMETER : .135 MAX (3,43)  
STRIP LENGHT : .236 (6,00)

TOOLING  
CRIMPING TOOL : M22520/1-01 (RADIALL 282 291)  
SELECTOR POSITION : 8 FOR AWG 12  
7 FOR AWG 14

POSITIONER : M22520/1-11 (RADIALL 282 579)

MATERIAL AND FINISHES :  
BODY CONTACT : BERYLLIUM COPPER PER ASTM-B-196 HEAT TREATED HARDNESS 380-420 HV  
BARREL ANNEALED HARDNESS 95-125 HV

PLATING : .00005 INCH OF GOLD PER SAE AMS-2422 OVER NICKEL PER SAE AMS-QQ-N-290

PROTECTIVE SLEEVE : PASSIVATED STAINLESS STEEL AISI 305

INSERTION/EXTRACTION TOOL : M81969/28-02 (RADIALL 282 547)  
SPL RADIALL EXT. 282 945



DIMENSIONS : mm (inch are given for information only)

CREATION

PEN:

NOM: VALGRESY

DATE: AUG 20 2008

APPR.: BROCHET

Issue	Revisions	Name	Approved
/	/	/	/
/	/	/	/
/	/	/	/
/	/	/	/
/	/	/	/