






Shell size	D Connectors Thread in inches	ØQ Max	ØB ±0.2	L	K ±0.2	M ±0.2	M1 ±0.2	A max	ØF cable max dimension
10SL	5/8”-24 UNEF	22	20	51	2.8	9.9	14.2	22.5	5.6
14S	7/8”-20 UNEF	29	24	54.5	3.2	11.4	14.5	28	7.9
16S	1”-20 UNEF	31	27	56	3.2	11.4	14.2	30	11
16	1”-20 UNEF	31	27	63.5	3.2	15.9	19	30	11
18	**1”1/8-18 UNEF**	**34**	**30**	**66.5**	**4**	**15.9**	**19**	**31.7**	**14.2**
20	1”1/4-18 UNEF	37	32	66.5	4	15.9	19	37.5	15.8
22	1”3/8-18 UNEF	40	37	69.5	4	15.9	19.7	37.5	15.8
24	1”1/2-18 UNEF	44	40	69.5	4	15.9	20.6	43.5	19
28	1”3/4-18 UNS	49.5	45	77.5	4	15.9	20.6	43.5	19
32	2”-18 UNS	56	52	78.5	4	15.9	22.2	51.7	23.8
36	2”1/4-16 UN	62.5	58	78.5	4	15.9	22.2	58.5	31.7
40	2”1/2-16 UN	68.5	63.2	92	4	15.9	22.2	68.5	34.9

Dimensions in mm

Dimension “L” can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.


Inserts



Arrangement	18-1
Gender	Socket
No. of contacts	10
Contacts size	N° 10 x #16 (22A Max)
Service Rating	B,C,F,G=A - Bal.=I
	B,C,F,G=700 Vdc - Bal.=250Vdc
	B,C,F,G=500 Vac - Bal.=200Vac
Rotation	N (0°)

Contacts P/N	Qty	Size	Termination	mm² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST385 16S	10	16	solder	-	18÷16	7	-	-	-	-	-

Grommet *



** Consult our sales office for wire specification*

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Code details

Insert material	_	Chloroprene rubber
Series	CVS	Thread connectors
Shell material	_	Aluminum alloy
Shell Type	01	In-line receptacle able to accept rear accessories
Connector Class	F	Backshell provided with MS3057..A type cable-clamp, bushing MS 3420.., grommet and cone
Accessories	_	-
Accessories	_	-
Accessories	_	-
Insert	18-1	Arrangement 18-1
Gender Contacts	S	Socket
Polarization	_	N (0°)
Backshell Details	_	-
Contacts Termination	_	Solder
Contact Plating	_	Silver 3.5µ min
Shell Finish	F4	CCF green (conductive)
Panel Gasket	_	-
Contact modification code	_	-
Customization	_	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Shell type:
Thread connectors
In-line receptacle able to accept rear accessories

Reference Documents:
- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529

General features:
Arrangement: 18-1; Socket; the insert is supplied with rotation: N (0°)
Contact: n.10 size 16; Solder

Operating temperatures: -55°C ÷ +125°C
Protection (mated connectors with adequate accessories): non enviromental
Insulating rubber parts: Chloroprene rubber

Connector supplied with:
- Backshell provided with MS3057..A type cable-clamp, bushing MS 3420.., grommet and cone

Electrical specifications:
Nominal Voltage: B,C,F,G=700 Vdc - Bal.=250 Vdc / B,C,F,G=500 Vac - Bal.=200 Vac (service B,C,F,G=A - Bal.=I)
Test Voltage: B,C,F,G=2000 Vac - Bal.=1000 Vac

Current Rating, single contact:
- maximum current: 22A (#16) with ambient temperature 20°C
- rated current: 13A (#16) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES
Shells	Aluminum alloy	CCF green (conductive)
Insulating	Chloroprene rubber	-
Contacts	Copper alloy	Silver 3.5µ min
Panel Gasket	-	-
Others part	-	-

ACCESSORIES (included)		
P/N	**Description**	**Quantity**
-	-	-
-	-	-
-	-	-

PACKAGING		
Quantity	**Type**	**Weight**
1	Plastic Bags	-
-	Carton Box	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.