







Panel cut out






Shell size	D Connectors Thread in inches	ØC ±0.2	K ±0.2	L	M ±0.2	ØN Max	R ±0.1	S ±0.3	ØT ±0.2	ØT1 Through holes
10SL	5/8"-24 UNEF	17	2.8	24.6	9.9	15.9	18.2	25.4	3.1	3.4
14S	7/8"-20 UNEF	20	3.2	24.6	11.4	19.2	23	30.2	3.1	3.4
16S	1"-20 UNEF	23	3.2	24.6	11.4	22.4	24.6	32.5	3.1	3.4
16	1"-20 UNEF	23	3.2	34.1	15.9	22.4	24.6	32.5	3.1	3.4
18	1"1/8-18 UNEF	26.5	4	34.1	15.9	25.6	27	34.9	3.1	3.4
20	1"1/4-18 UNEF	30	4	34.3	15.9	29	29.4	38.1	3.1	3.4
22	1"3/8-18 UNEF	33	4	34.3	15.9	32.2	31.8	41	3.1	3.4
24	1"1/2-18 UNEF	36	4	35.8	15.9	35.3	34.9	44.5	3.7	3.9
28	1"3/4-18 UNEF	42	4	35.8	15.9	41.4	39.7	50.8	3.7	3.9
32	2"-18 UNS	48.5	4	37.6	15.9	47.8	44.5	57	4.4	4.5
36	2"1/4-16 UN	55	4	37.6	15.9	52.4	49.2	63.5	4.4	4.5
40	2"1/2-16 UN	61	4	37.6	15.9	59	55.6	69.8	4.4	4.5

Dimensions in mm

Dimension "L" can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Inserts



Arrangement	14S-5
Gender	Socket
No. of contacts	5
Contacts size	N° 5 x #16S (22A Max)
Service Rating	I (250Vdc - 200Vac)
Rotation	0°

Contacts P/N	Qty	Size	Termination	mm² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST385 16SS	5	16S	solder	-	18÷16	5,5	-	-	-	-	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Code details

Insert material	_	Chloroprene rubber
Series	CVS	Thread connectors
Shell material	_	Aluminum alloy
Shell Type	02A	Front mounting receptacle connector non enviromental (equivalent MS3102A version)
Connector Class		No rear accessories
Accessories	_	-
Accessories	_	-
Accessories	_	-
Insert	14S-5	Arrangement 14S-5
Gender Contacts	S	Socket
Polarization	_	N (0°)
Backshell Details	_	-
Contacts Termination	_	Solder
Contact Plating	_	Silver 3.5µ min
Shell Finish	F16	CCF black, conductive - RoHS compliant
Panel Gasket	_	-
Contact modification code	_	-
Customization	_	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Shell type:
Thread connectors
Front mounting receptacle connector non enviromental (equivalent MS3102A version)

Reference Documents:
- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529
- Direttiva Europea 2011/65/UE (RoHS)

General features:
Arrangement: 14S-5; Socket; the insert is supplied with rotation: N (0°)
Contact: n.5 size 16S; Solder

Operating temperatures: -55°C ÷ +125°C
Protection degree (mated connectors; according to EN 60529):
Insulating rubber parts: Chloroprene rubber

Connector supplied with:
No rear accessories

Electrical specifications:
Nominal Voltage: 250 Vdc / 200 Vac (service I)
Test Voltage: 1000 Vac
Current Rating, single contact:
- maximum current: 22A (#16S) with ambient temperature 20°C
- rated current: 13A (#16S) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES
Shells	Aluminum alloy	CCF black, conductive - RoHS compliant
Insulating	Chloroprene rubber	-
Contacts	Copper alloy	Silver 3.5µ min
Panel Gasket	-	-
Others part	-	-

ACCESSORIES (included)		
P/N	**Description**	**Quantity**
-	-	-
-	-	-
-	-	-

PACKAGING		
Quantity	**Type**	**Weight**
1	Plastic Bags	-
-	Carton Box	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.