




| Shell size | D<br>Connectors<br>Thread in inches | ØQ<br>±0.2 | ØB<br>±0.2 | L<br>max | N<br>Backshell<br>Thread in inches |
|---|---|---|---|---|---|
| 10SL | 5/8”-24 UNEF | 22.8 | 20 | 36 | 5/8”-24 UNEF |
| 14S | 7/8”-20 UNEF | 28.5 | 24 | 43 | 3/4”-20 UNEF |
| 16S | 1”-20 UNEF | 31.8 | 27 | 43 | 7/8”-20 UNEF |
| 16 | 1”-20 UNEF | 31.8 | 27 | 49 | 7/8”-20 UNEF |
| 18 | 1”1/8-18 UNEF | 34 | 30 | 52 | 1”-20 UNEF |
| 20 | 1”1/4-18 UNEF | 37.3 | 32 | 52.5 | 1” 3/16-18 UNEF |
| 22 | 1”3/8-18 UNEF | 40.5 | 37 | 55 | 1” 3/16-18 UNEF |
| **24** | **1”1/2-18 UNEF** | **43.5** | **40** | **55** | **1” 7/16-18 UNEF** |
| 28 | 1”3/4-18 UNS | 50 | 45 | 62 | 1” 7/16-18 UNEF |
| 32 | 2”-18 UNS | 56.1 | 52 | 62 | 1” 3/4-18 UNS |
| 36 | 2”1/4-16 UN | 62.5 | 58 | 62 | 2”-18 UNS |
| 40 | 2”1/2-16 UN | 69.1 | 63.8 | 64 | 2”1/4-16 UN |

***Dimensions in mm***

***Dimension “L” can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.***

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

## Inserts




| | |
|---|---|
| **Arrangement** | 24-10 |
| **Gender** | Socket |
| **No. of contacts** | 7 |
| **Contacts size** | N° 7 x #8 (73A Max) |
| | |
| | |
| **Service Rating** | A (700Vdc - 500Vac) |
| | |
| | |
| **Rotation** | N (0°) |

| Contacts P/N | Qty | Size | Termination | mm² section | AWG section | Stripping length mm | Manual crimp tool | Crimp Die / Locator | Insertion tool | Removal tool | Guide pin |
|---|---|---|---|---|---|---|---|---|---|---|---|
| ST485 8S CD5 | 7 | 8 | crimp | - | 8 | 12 | CRT-HT45 | CDI-ME2 | CTIN-784-8 | CTES-784-8 | - |
| | | | | | | | | | | | |

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

## Code details

| | | |
|---|---|---|
| Insert material | _ | Chloroprene rubber |
| Series | CVS | Thread connectors |
| Shell material | _ | Aluminum alloy |
| Shell Type | 06 | Plug connector for straight backshell, with coupling nut |
| Connector Class | DA | Standard backshell having an external thread suitable for MS3057...A or C type cable-clamps, with waterproof O-ring |
| Accessories | _ | - |
| Accessories | _ | - |
| Accessories | _ | - |
| Insert | 24-10 | Arrangement 24-10 |
| Gender Contacts | S | Socket |
| Polarization | _ | N (0°) |
| Backshell Details | _ | - |
| Contacts Termination | CR | Crimp |
| Contact Plating | CD5 | Nickel + gold 0.4 µ min |
| Shell Finish | F16 | CCF black, conductive - RoHS compliant |
| Panel Gasket | _ | - |
| Contact modification code | _ | - |
| Customization | _ | - |

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

**Shell type:**
Thread connectors
Plug connector for straight backshell, with coupling nut

**Reference Documents:**
- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529
- European Directive 2011/65/UE (RoHS)

**General features:**
Arrangement: 24-10; Socket; the insert is supplied with rotation: N (0°)
Contact: n.7 size 8; Crimp

Operating Temperature: -55 ÷ +125°C
IP Protection degree according EN60529: IP67
Insulating rubber parts: Chloroprene rubber

**Connector supplied with:**
- Standard backshell having an external thread suitable for MS3057...A or C type cable-clamps, with waterproof O-ring

**Electrical specifications:**
Nominal Voltage: 700 Vdc / 500 Vac (service A)
Test Voltage: 2000 Vac

Current Rating, single contact:
- maximum current: 73A (#8) with ambient temperature 20°C
- rated current: 46A (#8) with ambient temperature 80°C

| COMPONENTS | MATERIALS | PLATING / FINISHES |
|---|---|---|
| Shells | Aluminum alloy | CCF black, conductive - RoHS compliant |
| Insulating | Chloroprene rubber | - |
| Contacts | Copper alloy | Nickel + gold 0.4 µ min |
| Panel Gasket | - | - |
| Others part | - | - |

| ACCESSORIES (included) | | |
|---|---|---|
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |

| PACKAGING | | |
|---|---|---|
| **Quantity** | **Type** | **Weight** |
| 1 | Plastic Bags | - |
| - | Carton Box | - |



This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.