






Shell size	D Connectors Thread in inches	ØQ ±0.2	ØB ±0.2	L max	N Backshell Thread in inches
10SL	5/8”-24 UNEF	22.8	20	36	5/8”-24 UNEF
14S	**7/8”-20 UNEF**	**28.5**	**24**	**43**	**3/4”-20 UNEF**
16S	1”-20 UNEF	31.8	27	43	7/8”-20 UNEF
16	1”-20 UNEF	31.8	27	49	7/8”-20 UNEF
18	1”1/8-18 UNEF	34	30	52	1”-20 UNEF
20	1”1/4-18 UNEF	37.3	32	52.5	1” 3/16-18 UNEF
22	1”3/8-18 UNEF	40.5	37	55	1” 3/16-18 UNEF
24	1”1/2-18 UNEF	43.5	40	55	1” 7/16-18 UNEF
28	1”3/4-18 UNS	50	45	62	1” 7/16-18 UNEF
32	2”-18 UNS	56.1	52	62	1” 3/4-18 UNS
36	2”1/4-16 UN	62.5	58	62	2”-18 UNS
40	2”1/2-16 UN	69.1	63.8	64	2”1/4-16 UN

Dimensions in mm

Dimension “L” can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Inserts



Arrangement	14S-6
Gender	Socket
No. of contacts	6
Contacts size	N° 6 x #16S (22A Max)
Service Rating	I (250Vdc - 200Vac)
Rotation	N (0°)

Contacts P/N	Qty	Size	Termination	mm² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST485 16SS CD5	6	16S	crimp	1÷1.5	18÷16	6.3	CRT-784/1	LOC-784	CTIN-784-16	CTES-784-16	GP-784-16

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Code details

Insert material	RF	Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
Series	CVS	Thread connectors
Shell material	_	Aluminum alloy
Shell Type	06	Plug connector for straight backshell, with coupling nut
Connector Class	DA	Standard backshell having an external thread suitable for MS3057...A or C type cable-clamps, with waterproof O-ring
Accessories	_	-
Accessories	_	-
Accessories	_	-
Insert	14S-6	Arrangement 14S-6
Gender Contacts	S	Socket
Polarization	_	N (0°)
Backshell Details	_	-
Contacts Termination	CR	Crimp
Contact Plating	CD5	Nickel + gold 0.4 µ min
Shell Finish	F16	CCF black, conductive - RoHS compliant
Panel Gasket	_	-
Contact modification code	_	-
Customization	_	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Shell type:
Thread connectors
Plug connector for straight backshell, with coupling nut

Reference Documents:
- SAE AS 50151 (ex MIL-C-5015 where applicable)
- EN 60529
- EN45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
- European Directive 2011/65/UE (RoHS)

General features:
Arrangement: 14S-6; Socket; the insert is supplied with rotation: N (0°)
Contact: n.6 size 16S; Crimp

Operating Temperature: -55 ÷ +150°C
IP Protection degree according EN60529: IP67
Insulating rubber parts: Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)

Connector supplied with:
- Standard backshell having an external thread suitable for MS3057...A or C type cable-clamps, with waterproof O-ring

Electrical specifications:
Nominal Voltage: 250 Vdc / 200 Vac (service I)
Test Voltage: 1000 Vac

Current Rating, single contact:
- maximum current: 22A (#16S) with ambient temperature 20°C
- rated current: 13A (#16S) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES
Shells	Aluminum alloy	CCF black, conductive - RoHS compliant
Insulating	Fire behaviour* (fire and smoke)	-
Contacts	Copper alloy	Nickel + gold 0.4 µ min
Panel Gasket	-	-
Others part	-	-

ACCESSORIES (included)		
-	-	-
-	-	-
-	-	-
-	-	-

** Insulating Class parts: fire behaviour (fire and smoke) complying with EN 45545-2 Par. 4.3.1 (< 10 g), NFPA130 Par. 8.4.1.10 (< 100 cm²)*

PACKAGING		
Quantity	**Type**	**Weight**
1	Plastic Bags	-
-	Carton Box	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.