



PAGE **1/4**	ISSUE **16-10-19A**	SERIES **CVB**	PART NUMBER **CVB 02A 22-22S F4**





Panel cut out






Shell size	ØD	L ±0.3	K ±0.2	M ±0.2	ØN Max	S ±0.3	R ±0.1	ØT ±0.2	ØT1 Through holes	ØC ±0.2
10SL	18.2	25	2.8	14.2	16.3	25.4	18.2	3.1	3.4	17
14S	24.6	25	3.2	14.5	19.2	30.2	23	3.1	3.4	20
16S	27.4	24.7	3.2	14.2	22.4	32.5	24.6	3.1	3.4	23
16	27.4	34	3.2	19	22.4	32.5	24.6	3.1	3.4	23
18	30.8	34.3	4	19	25.6	34.9	27	3.1	3.4	26.5
20	34.2	34.3	4	19	28.8	38.1	29.4	3.1	3.4	30
22	**37.4**	**34.3**	**4**	**19.7**	**32.2**	**41**	**31.8**	**3.1**	**3.4**	**33**
24	40.9	36	4	20.6	35.2	44.5	34.9	3.7	3.9	36
28	46.7	36	4	20.6	41.5	50.8	39.7	3.7	3.9	42
32	53.4	37.5	4	22.2	47.8	57	44.5	4.4	4.5	48.5
36	59.6	37.5	4	22.2	52.6	63.5	49.2	4.4	4.5	55
40	65.5	37.5	4	22.2	59.2	69.8	55.6	4.4	4.5	61

Dimensions in mm

Dimension "L" can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Inserts



Arrangement	22-22
Gender	Socket
No. of contacts	4
Contacts size	N° 4 x #8 (73A Max)
Service Rating	A (700Vdc - 500Vac)
Rotation	N (0°)

Contacts P/N	Qty	Size	Termination	mm² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST385 8S	4	8	solder	-	8	12,6	-	-	-	-	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Code details

Insert material	_	Chloroprene rubber
Series	CVB	Bayonet connector
Shell material	_	Aluminum alloy
Shell Type	02A	Front mounting receptacle connector non enviromental (equivalent MS3102A version)
Connector Class	_	No rear accessories
Accessories	_	-
Accessories	_	-
Accessories	_	-
Insert	22-22	Arrangement 22-22
Gender Contacts	S	Socket
Polarization	_	N (0°)
Backshell Details	_	-
Contacts Termination	_	Solder
Contact Plating	_	Silver 3.5µ min
Shell Finish	F4	CCF green (conductive)
Panel Gasket	_	-
Contact modification code	_	-
Customization	_	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Shell type:
Bayonet connector
Front mounting receptacle connector non enviromental (equivalent MS3102A version)

Reference Documents:
- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529

General features:
Arrangement: 22-22; Socket; the insert is supplied with rotation: N (0°)
Contact: n.4 size 8; Solder

Operating temperatures: -55°C ÷ +125°C
Insulating rubber parts: Chloroprene rubber

Connector supplied with:
- No rear accessories

Electrical specifications:
Nominal Voltage: 700 Vdc / 500 Vac (service A)
Test Voltage: 2000 Vac

Current Rating, single contact:
- maximum current: 73A (#8) with ambient temperature 20°C
- rated current: 46A (#8) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES
Shells	Aluminum alloy	CCF green (conductive)
Insulating	Chloroprene rubber	-
Contacts	Copper alloy	Silver 3.5µ min
Panel Gasket	-	-
Others part	-	-

ACCESSORIES (included)		
P/N	**Description**	**Quantity**
-	-	-
-	-	-
-	-	-

PACKAGING		
Quantity	**Type**	**Weight**
1	Plastic Bags	-
-	Carton Box	-

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall VanSystem S.r.l. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.