





PAGE 1/4

ISSUE 20-09-21A

SERIES RF CVBS

PART NUMBER RF CVBS 030 22-14P CR CD5 F16



Shell size	ØD +0 -0.15	L	K ±0.2	M ±0.2	N Thread in inches	R ±0.1	S ±0.3	ØT	ØT1	ØC ±0.2	P Panel Thickness Max
10SL	18.2	30	2.8	18.2	5/8"-24 UNEF	18.2	25.4	M4	4.5	19.1	6
14S	24.6	30	3.2	18.6	3/4"-20 UNEF	23	30.2	M4	4.5	25.5	7.2
16S	27.4	30	3.2	18.6	7/8"-20 UNEF	24.6	32.5	M4	4.5	28.3	7.2
16	27.4	38.8	3.2	23.05	7/8"-20 UNEF	24.6	32.5	M4	4.5	28.3	5.35
18	30.8	38.5	4	23.4	1"-20 UNEF	27	34.9	M4	4.5	31.7	7.25
20	34.2	39.1	4	23.4	1" 1/8-18 UNEF	29.4	38.1	M4	4.5	35	7.3
22	37.4	39.3	4	23.4	1" 1/4-18 UNEF	31.8	41	M4	4.5	38.3	7.3
24	40.9	38.8	4	23.4	1" 3/8-18 UNEF	34.9	44.5	M4	4.5	41.8	6.85
28	46.7	39.1	4	24.4	1" 5/8-18 UNEF	39.7	50.8	M5	5.5	47.6	7.8
32	53.4	38.4	4	24.4	1" 7/8-16 UN	44.5	57	M5	5.5	54.3	7.5
36	59.6	39.9	4	24.4	2" 1/16-16 UNS	49.2	63.5	M5	5.5	60.5	7.5
40	65.5	38.5	4	24.4	2" 5/16-16 UNS	55.6	69.8	M5	5.5	66.4	7.5

Dimensions in mm

Dimension "L" can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.


PAGE 2/4

ISSUE 20-09-21A

SERIES RF CVBS

PART NUMBER RF CVBS 030 22-14P CR CD5 F16

Inserts



Arrangement 22-14

Gender Pin

**No. of con-
tacts** 19

Contacts size N° 19 x #16 (22A Max)

Service Rating A (700Vdc - 500Vac)

Rotation N (0°)

Contacts P/N	Qty Size		Termination	mm ² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST485 16P CD5	19	16	crimp	1÷1.5	18÷16	6.3	CRT-784/1	LOC-784	CTIN-784-16	CTES-784-16	GP-784-16

PAGE 3/4

ISSUE 20-09-21A

SERIES RF CVBS

PART NUMBER RF CVBS 030 22-14P CR CD5 F16

Code details

Insert material	RF	Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
Series	CVBS	Bayonet connector with protected mating ramps
Shell material	–	Aluminum alloy
Shell Type	030	Rear mounting receptacle connector with thread to accept backshells
Connector Class	–	No rear accessories
Accessories	–	-
Accessories	–	-
Accessories	–	-
Insert	22-14	Arrangement 22-14
Gender Contacts	P	Pin
Polarization	–	N (0°)
Backshell Details	–	-
Contacts Termination	CR	Crimp
Contact Plating	CD5	Nickel + gold 0.4 µ min
Shell Finish	F16	CCF black, conductive - RoHS compliant
Panel Gasket	–	-
Contact modification code	–	-
Customization	–	-

PAGE 4/4

ISSUE 20-09-21A

SERIES RF CVBS

PART NUMBER RF CVBS 030 22-14P CR CD5 F16

Shell type:

Bayonet connector with protected mating ramps
 Rear mounting receptacle connector with thread to accept backshells

Reference Documents:

- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529
- EN45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
- European Directive 2011/65/UE (RoHS)

General features:

Arrangement: 22-14; Pin; the insert is supplied with rotation: N (0°)
 Contact: n.19 size 16; Crimp

Operating Temperature: -55 ÷ +150°C

Insulating rubber parts: Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)

Connector supplied with:

- No rear accessories

Electrical specifications:

Nominal Voltage: 700 Vdc / 500 Vac (service A)

Test Voltage: 2000 Vac

Current Rating, single contact:

- maximum current: 22A (#16) with ambient temperature 20°C
- rated current: 13A (#16) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES	ACCESSORIES (included)		
			P/N	Description	Quantity
Shells	Aluminum alloy	CCF black, conductive - RoHS compliant			
Insulating	Fire behaviour (fire and smoke)	-	-	-	-
Contacts	Copper alloy	Nickel + gold 0.4 µ min	-	-	-
Panel Gasket	-	-	-	-	-
Others part	-	-			

PACKAGING

Quantity	Type	Weight
1	Plastic Bags	-
-	Carton Box	-