


PAGE 1/4

ISSUE 14-07-20A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 14S-2S M16 CR CD5 F7



Without adapter

Shell size	ØQ ±0.2	L max	Z min	H1 max	H2 max	N Backshell Thread Metric	PG
10SL	23.3	45.5	7	26	40.3	M16	PG9
14S	29.5	45.5	7	26	40.3	M16	PG9
16S	33	47	-	-	-	-	-
16	33	56.5	-	-	-	-	-
18	37	57.5	7	31	48.1	M20	PG16
20	41	60	7	33	51.7	M25	-
22	43	62.5	7	35	55.3	M25	PG21
24	48	65.5	7	38	59.8	M32	PG21
28	53	65.5	7	40	65	M32	PG21
32	60	70	-	-	-	-	-
36	66.2	73.5	-	-	-	-	-
40	72.4	78.5	-	-	-	-	-

Dimensions in mm

Dimension "L" can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.


PAGE 2/4

ISSUE 14-07-20A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 14S-2S M16 CR CD5 F7


Inserts



Arrangement	14S-2
Gender	Socket
No. of contacts	4
Contacts size	N° 4 x #16S (22A Max)
Service Rating	I (250Vdc - 200Vac)
Rotation	N (0°)

Contacts P/N	Qty	Size	Termination	mm ² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
ST485 16SS CD5	4	16S	crimp	1÷1.5	18÷16	6.35	CRT-784/1	LOC-784	CTIN-784-16	CTES-784-16	GP-784-16

Grommet *



* Consult our sales office for wire specification

PAGE 3/4

ISSUE 14-07-20A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 14S-2S M16 CR CD5 F7

Code details

Insert material	RF	Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
Series	CVBS	Bayonet connector with protected mating ramps
Shell material	–	Aluminum alloy
Shell Type	08	Plug connector, with 90° elbow and coupling nut
Connector Class	RA	Backshell with waterproof o-ring, grommet and cone. Internal Metric thread M16
Accessories	–	–
Accessories	–	–
Accessories	–	–
Insert	14S-2	Arrangement 14S-2
Gender Contacts	S	Socket
Polarization	–	N (0°)
Backshell Details:	M16	Internal Metric thread M16
Contacts termination	CR	Crimp
Contacts plating	CD5	Nickel + gold 0.4 µ min
Shell Finish	F7	Black epoxy-polyurethane varnish (non conductive), RoHS compliant
Panel Gasket	–	–
Contact modification code	–	–
Customization	–	–

PAGE 4/4

ISSUE 14-07-20A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 14S-2S M16 CR CD5 F7

Shell type:

Bayonet connector with protected mating ramps
Plug connector, with 90° elbow and coupling nut

Reference Documents:

- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529
- EN45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
- European Directive 2011/65/UE (RoHS)

General features:

Arrangement: 14S-2; Socket; the insert is supplied with rotation: N (0°)
Contact: n.4 size 16S; Crimp

Operating temperatures: -55°C ÷ +125°C

Protection degree (mated connectors; according to EN 60529): IP67

Insulating rubber parts: Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)

Connector supplied with:

- Backshell with waterproof o-ring, grommet and cone. Internal Metric thread M16

Electrical specifications:

Nominal Voltage: 250 Vdc / 200 Vac (service I)

Test Voltage: 1000 Vac

Current Rating, single contact:

- maximum current: 22A (#16S) with ambient temperature 20°C
- rated current: 13A (#16S) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES	ACCESSORIES (included)		
			P/N	Description	Quantity
Shells	Aluminum alloy	Black epoxy-polyurethane varnish (non conductive), RoHS compliant			
Insulating	Fire behaviour (fire and smoke) *	-	-	-	-
Contacts	Copper alloy	Nickel + gold 0.4 µ min	-	-	-
Panel Gasket	-	-	-	-	-
Others part	-	-			

* Insulating Class parts: fire behaviour (fire and smoke) complying with EN 45545-2
Par. 4.3.1 (< 10 g), NFPA130 Par. 8.4.1.10 (< 100 cm²)

PACKAGING

Quantity	Type	Weight
1	Plastic Bags	-
-	Carton Box	-



Radiall VanSystem S.r.l. | www.vansystem.eu - www.radiall.com