



PAGE 1/4

ISSUE 18-06-21A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 32-5P LC F16



Shell size	ØQ ±0.2	L max	H1 max	H2 max	N Backshell Thread in inches
10SL	23.3	45.5	27	38.7	5/8"-24 UNEF
14S	29.5	45.5	27	41.3	3/4"-20 UNEF
16S	33	47	29	44.9	7/8"-20 UNEF
16	33	56.5	29	44.9	7/8"-20 UNEF
18	37	57.5	31	48.1	1"-20 UNEF
20	41	60	33	51.7	1" 3/16-18 UNEF
22	43	62.5	35	55.3	1" 3/16-18 UNEF
24	48	65.5	38	59.8	1" 7/16-18 UNEF
28	53	65.5	40	65	1" 7/16-18 UNEF
32	60	70	46	74.1	1" 3/4-18 UNS
36	66.2	73.5	49	80.3	2"-18 UNS
40	72.4	78.5	53	87.6	2"1/4-16 UN

Dimensions in mm

Dimension "L" can be different from the value indicated according to backshells accessories, wires size and some special insert configurations.


PAGE 2/4

ISSUE 18-06-21A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 32-5P LC F16


Inserts



Arrangement	32-5
Gender	Pin
No. of contacts	2
Contacts size	N° 2 x #0 (245A Max)
Service Rating	D (1250Vdc - 900Vac)
Rotation	N (0°)

Contacts P/N	Qty	Size	Termination	mm ² section	AWG section	Stripping length mm	Manual crimp tool	Crimp Die / Locator	Insertion tool	Removal tool	Guide pin
-	-	-	-	-	-	-	-	-	-	-	-

Grommet *



* Consult our sales office for wire specification

PAGE 3/4

ISSUE 18-06-21A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 32-5P LC F16

Code details

Insert material	RF	Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
Series	CVBS	Bayonet connector with protected mating ramps
Shell material	–	Aluminum alloy
Shell Type	08	Plug connector, with 90° elbow and coupling nut
Connector Class	RA	Standard backshell having an external thread suitable for MS3057...A or C type cacle clamps, with waterproof O-ring, grommet and cone
Accessories	–	–
Accessories	–	–
Accessories	–	–
Insert	32-5	Arrangement 32-5
Gender Contacts	P	Pin
Polarization	–	N (0°)
Backshell Details:	–	–
Contacts termination	LC	Less contacts (to be purchased separately)
Contacts plating	–	–
Shell Finish	F16	CCF black, conductive - RoHS compliant
Panel Gasket	–	–
Contact modification code	–	–
Customization	–	–

PAGE 4/4

ISSUE 18-06-21A

SERIES RF CVBS

PART NUMBER RF CVBS 08RA 32-5P LC F16

Shell type:

Bayonet connector with protected mating ramps
Plug connector, with 90° elbow and coupling nut

Reference Documents:

- Mil-DTL-5015 (where applicable)
- VG 95234 (where applicable)
- EN 60529
- EN45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)
- European Directive 2011/65/UE (RoHS)

General features:

Arrangement: 32-5; Pin; the insert is supplied with rotation: N (0°)
Contact: n.2 size 0; Less contacts (to be purchased separately)

Operating Temperature: -55 ÷ +150°C

Protection (mated connectors with adequate accessories): IP67

Insulating rubber parts: Fire behaviour (fire and smoke) complying with EN 45545-2, NFPA130 (ASTME162, ASTME662, BSS7239)

Connector supplied with:

- Standard backshell having an external thread suitable for MS3057...A or C type cable clamps, with waterproof O-ring, grommet and cone

Electrical specifications:

Nominal Voltage: 1250 Vdc / 900 Vac (service D)

Test Voltage: 2800 Vac

Current Rating, single contact:

- maximum current: 245A (#0) with ambient temperature 20°C
- rated current: 150A (#0) with ambient temperature 80°C

COMPONENTS	MATERIALS	PLATING / FINISHES	ACCESSORIES (included)		
			P/N	Description	Quantity
Shells	Aluminum alloy	CCF black, conductive - RoHS compliant			
Insulating	Fire behaviour * (fire and smoke)	-	-	-	-
Contacts	-	-	-	-	-
Panel Gasket	-	-	-	-	-
Others part	-	-			

* Insulating Class parts: fire behaviour (fire and smoke) complying with EN 45545-2
Par. 4.3.1 (< 10 g), NFPA130 Par. 8.4.1.10 (< 100 cm²)

PACKAGING

Quantity	Type	Weight
1	Plastic Bags	-
-	Carton Box	-