

This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

2 W

DC-12.4GHz


SMA

COAXIAL ATTENUATOR

issue  
28. jul. 93

Page  
1 / 1

**DRAWING**



General tolerances: +/- 0.5 mm

**R F CHARACTERISTICS**

FREQUENCY RANGE : DC - 12.4 GHz  
 IMPEDANCE : 50 Ohms  
 ATTENUATION - NOMINAL : 4 dB

|                |             |             |
|----------------|-------------|-------------|
| FREQUENCY      | DC- 4 GHz   | 4 -12.4GHz  |
| V.S.W.R        | <= 1.15     | <= 1.25     |
| DEVIATION (dB) | +0.3 / -0.3 | +0.3 / -0.3 |

TEMPERATURE SENSITIVITY :  $4 \times 10^{-4}$  dB / (dB \* °C)  
 PEAK POWER at 25°C (1µs,1%.) : 100 W  
 AVERAGE POWER at 25°C : 2 W


**MECHANICAL CHARACTERISTICS**

CONNECTORS : SMA male/female per MIL-C 39012  
 WEIGHT : < 5 g

**ENVIRONMENTAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE (°C) : -55 , +125  
 STORAGE TEMPERATURE RANGE (°C) : -55 , +125

Power derating  
Versus temperature



QUALITY Dpt app  
 CREATION  
 PEN : CAT  
 EP :  
 Nom : DP  
 Date : 02.mar.89

28.jul.93  
**ISSUE**

New format

**REVISIONS**

VE  
**NAME**

**RADIALL®**

101. Philibert Hoffmann - Z.I Ouest - 93116 ROSNY/BOIS Codex-FRANCE  
 Phone: 33.1.49353535 Fax : 33.1.48546363  
 Tlx RADIA 235220F